



CONTEG[®]
to complete your network

Headquarters in Prague, Czech Republic

Tel.: +420 261 219 182, Fax: +420 261 219 192
conteg@conteg.com, www.conteg.com

Austria	+43 2243 21203
Czech Republic	+420 261 219 182
Eastern Europe	+49 172 848 4346
France	+33 686 074 386
Germany, Switzerland	+49 170 523 4958
Middle East	+971 50 871 4563
Russia	+7 495 506 13 28
Western Europe	+420 261 219 182

Cut Sheet

TRANSPORT CASTORS DP-KO-TC

13_1_2010, CONTEG ©

INTRODUCTION

The transport castor wheels support mobility of the free standing racks on the final place of installation. They are easy to use to maintain mobility of the cabinets.

KEY FEATURES

- Easy to use and install
- Quick move on the site
- Save your time

APPLICATIONS

The transport castors are recommended in dynamic datacenters and server rooms with emphasis in saving time. Also is the right choice when transporting a rack from input gate to the final place of installation.

DESCRIPTION

Load rating - per castor 30kg, optimum for standard rack is 4 pieces. Castor is not usable for continuous loading – only for installation on moving process of the rack.

Compatibility - the transport castors are fully compatible with the wide range of CONTEG free standing racks. Specially they are recommended for CONTEG's facelifted ROF rack family (RDF, RHF, ROR) launched in the end of 2009.

Size - 40x73x85mm (WxDxH), for height with rack add 70mm to rack's height.

Packaging - 4x castors, 1x spanner.

Colors - white castor fixing in zincoïd body.



TECHNICAL SPECIFICATIONS

Wheel Ø	50 mm
Wheel width	40 mm
Load capacity	30 kg per castor
Bearing version	Ball bearing
Total height	85 mm
Bolt hole Ø	10,2 mm
Offset	34 mm
Plate Ø	55 mm