

# OPTIMAL PC ROP



ROP-36-65/60

➤ The **OPTIMAL PC ROP** is designed to both securely house and safely position a personal computer without user limitation, with the possibility of installing standard 19" equipment.



## MAIN ADVANTAGES

- Special solution to securely house PCs
- Three compartments for specific use

COLOR SAMPLER: RAL 7035

Code	H (in U)	Dimensions (mm)				Dimensions including packing (mm)			Gross weight (kg)
		H*	W	D	Useful depth	H	W	D	
ROP-36-65/60	36	1721	650	600	590	1850	690	660	105

\* Height in mm without feet; for feet add 16–45 mm

## DESCRIPTION:

- |  |  |   |
|--|--|---|
| <p><b>Sizes</b></p> <ul style="list-style-type: none"> <li>• Height: 36U</li> <li>• Width: 650 mm</li> <li>• Depth: 600 mm</li> </ul> <p><b>Construction</b></p> <ul style="list-style-type: none"> <li>• Welded-frame design</li> <li>• 1.5 &amp; 2.0 mm sheet steel</li> </ul> <p><b>IP rating</b></p> <ul style="list-style-type: none"> <li>• Standard IP30</li> </ul> <p><b>Load rating</b></p> <ul style="list-style-type: none"> <li>• Frame – 400 kg</li> <li>• Bottom section – 300 kg</li> <li>• Top section – 100 kg</li> </ul> | <ul style="list-style-type: none"> <li>• Pull-out shelf – 10 kg</li> </ul> <p><b>Colors</b></p> <ul style="list-style-type: none"> <li>• Standard RAL 7035</li> <li>• Other colors optional</li> </ul> <p><b>Front door</b></p> <ul style="list-style-type: none"> <li>• Tinted security glass door with swivel handle lock – top part (12U)</li> <li>• Sheet steel door with swivel handle lock – bottom part (22U)</li> <li>• Door opening angle 180°</li> <li>• Lockable 2U pull-out shelf</li> </ul> <p><b>Rear panel</b></p> <ul style="list-style-type: none"> <li>• Removable, with lock</li> </ul> | <ul style="list-style-type: none"> <li>• Sheet steel or perforated sheet steel</li> </ul> <p><b>Side panels</b></p> <ul style="list-style-type: none"> <li>• Removable, with lock</li> <li>• Sheet steel or perforated sheet steel</li> </ul> <p><b>Cable entries</b></p> <ul style="list-style-type: none"> <li>• In top and bottom plate</li> <li>• Covered by removable blank panels</li> </ul> <p><b>Ventilation unit openings</b></p> <ul style="list-style-type: none"> <li>• In top and bottom plate</li> <li>• All ventilation unit openings covered by removable blank panels</li> </ul> <p><b>Feet</b></p> <ul style="list-style-type: none"> <li>• Adjustable feet standard</li> </ul> |
|--|--|---|

[www.conteg.com](http://www.conteg.com)



**CONTEG, spol. s r.o.**

**Headquarters:**

Na Vítěznej pláni 1719/4  
140 00 Prague 4  
Czech Republic  
Tel.: +420 261 219 182  
[conteg@conteg.com](mailto:conteg@conteg.com)  
[www.conteg.com](http://www.conteg.com)

**Production plant:**

K Silu 2179  
393 01 Pelhřimov  
Czech Republic  
Tel.: +420 565 300 300

**Local Branches/Offices:**

Austria/Germany/Switzerland:	+420 261 219 182
Benelux:	+31 76 5420 709
Southeastern Europe:	+49 172 8484 346
Finland:	+358 50 414 1257
France/Italy/Maghreb:	+33 1 60 04 55 90
Middle East:	+971 55 508 3241
Russia/CIS:	+7 495 967 3840
Saudi Arabia:	+966 54 000 2341

**CONTEG**